



Main

Range	Exiway
Product name	Exiway Easyled
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Number of batteries	1 x 4.8 V 0.8 Ah Ni-Cd (Nickel-Cadmium)
Colour	White
Light source	LED : 8 W integral LED base
Light source colour	White
Cover type	Transparent

Complementary

Range compatibility	Remote control
[Ue] rated operational voltage	220...230 V at 50/60 Hz AC/DC
Power consumption in VA	2.5 VA
Power consumption in W	1.6 W
Current consumption	10 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	12 h
Luminous flux	Emergency condition : 120 lm
Type of glass	Serigraphed transparent glass
Material	Housing : plastic Cover : plastic
Device mounting	Surface ceiling Surface wall Flush false ceiling

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Flush wall
Height	116 mm
Width	292 mm
Depth	37 mm
Product weight	0.5 kg

Environment

IP degree of protection	IP65
IK degree of protection	IK07
Ambient air temperature for operation	0...40 °C
Fire resistance	850 °C
Product certifications	ENEC
Standards	IEC 60695-2-10 EN/IEC 60598-2-22

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1404 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------